



**Solution Dyed Polyester  
Formulated to withstand the Elements.  
Ideal for Outdoor Applications.**



**MARINE - AWNING - SHADE - COVERS**

**Fabric Components:**

|              |                       |                |                         |
|--------------|-----------------------|----------------|-------------------------|
| Total Weight | 7.5 +/-0.50 oz./sq.yd | Coating Weight | 0.60 +/-15% oz./sq.yd.  |
| Fiber        | 100% Polyester        | Finish         | DWR, UC, Anti Microbial |
| Weave        | Plain                 | Width          | 61/62"                  |

**Mechanical Properties:**

| Characteristic       |           | Test Method | Results             |
|----------------------|-----------|-------------|---------------------|
| Grab Tensile         | Warp Fill | ASTM D5034  | 407 Lbs. / 232 Lbs. |
| Tongue Tear          | Warp Fill | ASTM D2261  | 17 Lbs. / 12 Lbs.   |
| Color Fastness       |           | AATCC 16E   | Excellent           |
| Hydrostatic Pressure |           | AATCC 127   | 800+ mm             |
| Anti Microbial       |           | AATCC 30    | Pass                |



**Warranty-** Sunmaster™ has a limited 3 year warranty from the original date of purchase. Warranty covers fabric being unserviceable due to loss of strength and/or color from normal conditions of exposure to sunlight, rain and mildew. Warranty does not cover acts of god, vandalism, neglect or improper use. End user is responsible for proper care and maintenance. Warranty covers replacement of fabric only and does NOT include labor or installation or other consequential or incidental expenses. The RED color only features a 2 year limited warranty

**Notice: Warranty valid only if the invoice for the item purchased is submitted showing date of original purchase and installation.**

**Maintenance:** We recommend that Sunmaster be retreated annually with 303<sup>R</sup> or similar products to restore water repellency and yield best performance.

**Care and Cleaning:** Add 2 oz of mild soap (Woolite or Dawn) to 1 Gallon lukewarm water. Scrub gently with a soft brush. Rinse well with cold water. Air Dry.

BAYAMON  
785-5823

CAGUAS  
744-5680

CAROLINA  
768-3700

MAYAGUEZ  
831-7380

PONCE  
841-8206

SAN JUAN  
783-8565

VEGA BAJA  
855-5848

**DISCLAIMER**

The information provided represents typical physical properties but does not constitute a specification. Seller makes no representation, expressed or implied, that the products herein are suitable for the Buyer's intended use or that the products will be properly used by the Buyer for that purpose. The Buyer is solely responsible for determining the suitability of this product for their intended use. Any minimum performance requirements must be communicated by the buyer and agreed upon in writing by Super Plastico, Inc. when orders are placed. No liability will be accepted for errors and omissions and in no circumstances shall Super Plastico, Inc. be held liable for any loss or injury arising directly or indirectly as a consequence of the publication of this data sheet. We retain the right to change sizes and specifications of product without prior notification.